

**METHOD OF ENABLING AN INTERMEDIARY SERVER TO IMPERSONATE
A CLIENT USER'S IDENTITY TO A PLURALITY OF AUTHENTICATION
DOMAINS**

5 **BACKGROUND OF THE INVENTION**

Technical Field

The present invention relates generally to method of
accessing resources in a distributed computer networking
environment and, in particular, to a technique for
10 enabling an intermediary server to impersonate a client
user's identity to a plurality of authentication domains.

Description of the Related Art

Information technology (IT) systems and the Internet
have fueled the growth of the current global economy. In
15 a typical enterprise environment, however, there may be a
number of different business units, each offering a
different type of web-based business service or
application. Thus, for example, a large enterprise may
have a sales department, a service department, and so on.
20 Each department or business unit may also have their own
legacy or other backend system. Many such enterprises
have provided web-based business services through
distinct and often independent service offerings.
Continuing with the above example, the enterprise may
25 provide a first web-based business service through a
first portal, a second web-based business service through

a second portal, and so on. In such case, a given user may have multiple accounts and perhaps multiple passwords within the same enterprise as a result of the differences in backend systems, service offerings, and the like.

5 While these disparate systems provide users with adequate service offerings, a problem arises if the Company desires to combine these web-based business services into an integrated portal. In particular, typically there is significant user resistance to having
10 to modify account identities and passwords once such authentication data is established and in use.

The present invention addresses this problem.

BRIEF SUMMARY OF THE INVENTION

An intermediary server operative within an enterprise computing environment acts as a gateway between a client terminal and a set of one or more backend resource managers, each of which may be associated with an authentication service. The intermediary server interfaces to a single sign-on (SSO) service, which stores authentication information (e.g., user identities and passwords) that the user of the client terminal needs to obtain access to resources managed by the resource managers. Thus, for example, the user may have a first userid/password pair to enable access to a first resource manager, and a second userid/password pair to enable access to a second resource manager, and so on. In operation, the intermediary server receives an access request and establishes the client terminal user's primary identity. By authenticating itself to the SSO service, the intermediary server uses that identity to obtain (from the SSO) a set of user secondary identities that are then used (by the intermediary server) to impersonate the user to each of the backend resource managers. Thus, from a perspective outside the enterprise, the intermediary server gives the user the appearance of having a single

user account having a single password when, in fact, within the enterprise the user may have multiple accounts, perhaps with multiple passwords.

According to the present invention, the single sign-
5 on (SSO) service, in effect, is co-opted by the intermediary server on behalf of the client terminal user to facilitate identity mapping and authentication within the enterprise environment. The invention takes advantage of the fact that the SSO service already knows
10 what information is required to impersonate the user in the enterprise's authentication domains.

In a representative embodiment, the intermediary server is a web portal and the resource managers are legacy systems within the enterprise environment. The
15 client terminal is connected to the web portal over a computer network, such as the Internet.

The foregoing has outlined some of the more pertinent objects and features of the present invention. These objects should be construed to be merely
20 illustrative of some of the more prominent features and applications of the invention. Many other beneficial results can be attained by applying the disclosed invention in a different manner or modifying the invention as will be described. Accordingly, other

5

10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference should be made to the following Detailed Description taken in

5 connection with the accompanying drawings in which:

Figure 1 is a known web-based computer environment;

Figure 2 is an enterprise computing environment in which the present invention is implemented using an intermediary server;

10 **Figure 3** is a flowchart illustrating a transaction flow according to the invention; and

Figure 4 is an alternative embodiment of the invention illustrating a high availability, load-balanced architecture for the delegation functionality.

15

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention may be implemented within a web-based transaction environment such as the Internet. As is well-known, in the Internet paradigm as illustrated in **Figure 1**, a client machine, such as machine **100**, may use an application, such as a web browser **102**, to access a server **104** via a computer network **106**. Network **106** typically includes other servers (not shown) for control of domain name resolution, routing and other control functions. A representative server **104** is a computer or workstation having at least one processor **108**, system memory (e.g., RAM) **120**, disk or other permanent storage **122**, I/O devices **124a-n**, an operating system **126**, a server program **128**, and an application programming interface (API) **130** that provides extensions to enable application developers to extend and/or customize the core functionality thereof through software programs including plug-ins, CGI programs, Java servlets, and the like. One such software program is an inventive delegation mechanism **132**, which enables the server to impersonate as will be described. In an illustrative embodiment, the delegation mechanism is implemented on native code in Java executable in a processor. The

inventive functionality, of course, may be part of the integral web server program.

A representative server machine is an IBM Netfinity platform running the Unix or Linux operating system and a
5 server program such as IBM WebSphere Version 2.0 or Apache. Of course, any other computer hardware or software may be used.

A representative client is a personal computer, notebook computer, Internet appliance or pervasive
10 computing device (e.g., a PDA or palm computer) that is Pentium-, PowerPC®- or RISC-based. The client includes an operating system such as Microsoft Windows, Microsoft Windows CE or PalmOS. A typical client includes a suite of Internet tools including a Web browser, such as
15 Netscape Navigator or Microsoft Internet Explorer, that has a Java Virtual Machine (JVM) and support for application plug-ins or helper applications. Communications between the client and the server typically conform to the Hypertext Transfer Protocol
20 (Version 1.0 or higher), and such communications may be made over a secure connection.

An enterprise environment **200** in which the present invention is implemented is illustrated in **Figure 2**. For illustrative purposes only, the enterprise environment

200 includes an intermediary server 202, a single sign-on (SSO) service 204, and a set of one or more resource managers 206a-n. A resource manager allows access to or otherwise controls a resource. Intermediary server 202
5 hosts the inventive delegation functionality, as will be seen. The intermediary server 202 may be a computer dedicated to providing the inventive functionality, or it may be an adjunct to another computer. In the preferred embodiment, the server 202 is a web server and the
10 delegation functionality is implemented in software, for example, as a set of program instructions executable in one or more processors of the web server. As illustrated in **Figure 2**, intermediary server 202 is connected to SSO service 204 over link 203 which, in a representative
15 embodiment, is a mutually authenticated Secure Sockets Layer (SSL) session, a Kerberos session, or any other known or later-developed secure link. Alternatively, the link 203 may be insecure, in which case the intermediary server 202 and the SSO service 204 may communicate by
20 encrypting communications using, for example, an asymmetric key encryption technique. A representative technique is PGP™ (Pretty Good Privacy).

Resource managers 206 typically are servers, and a given resource manager 206 typically has associated

therewith an authentication service **208**. In the illustrated embodiment, a given resource manager is a computer or process that interfaces to other resources (e.g., databases, storage devices, or the like) in a legacy system within the enterprise. Given resource managers **206** may share an authentication service **208**. Intermediary server **202** may also have an authentication service **210** associated therewith. Authentication service **210** may be the same as service **208**, but generally is a separate service. SSO service **204** may also include an authentication service. Preferably, intermediary server **202** is connected to a given resource manager **206** via secure link **205**, e.g., an SSL session, a Kerberos session, or the like.

A client terminal **212** accesses the intermediary server **202** via a computer network **215**, e.g., the Internet, an intranet, a virtual private network, or the like. As described above, the client terminal is a computer, e.g., a personal computer, a laptop computer, a handheld device having a wireless Internet connection, an Internet appliance, or the like. In an typical transaction, the intermediary server is a web server or portal that is accessed via a URL in a known manner. For purposes of illustration, it is assumed that an

authorized user of resources in the enterprise computing environment has a first user identity/password pair **216a** for use in an authentication domain managed by a first resource manager **206a**, a second user identity/password pair **216b** for use in an authentication domain managed by a second resource manager **206b**, and so on. As used herein, a "user" may be a person or program having an identity that is capable of being authenticated. An authentication domain is a set of servers that accept given credentials, or more generally, a collection of systems that share a single source of administrative responsibility for the assertion of given access privileges. The user identity/password pairs **216** are stored in a database **220** associated with or part of the SSO service **204**. One of ordinary skill in the art will appreciate that other types of user authentication information may be used in lieu of or in addition to the user identity/password pairs **216** depending on the nature of the authentication service(s) used to validate that the user is who he or she claims to be.

Figure 3 is a flowchart illustrating a representative transaction flow according to the present invention. The transaction flow begins at step **300** with a user of the client terminal (who claims an identity)

making a request to access a resource within the enterprise environment. At step **302**, the user is authenticated by the intermediary server **202**. Typically, intermediary server **202** uses authentication service **210**

5 to verify that the user is who he or she claims to be. The process of authenticating the client terminal user to the intermediary server is sometimes referred to as a "primary" logon, for reasons which will become clear. As a result of the user authentication, the intermediary

10 server **202** establishes a user primary "identity" (or "primary account identity"). As will be seen, the intermediary server continues to handle responses and requests between the client and resource managers after the original logon. At step **304**, the intermediary server

15 **202** itself performs a "primary" logon to the SSO service **204** via the secure link **203**. In particular, at step **304**, intermediary server **202** goes to the SSO service **204** (under its own identity) for the purpose of authenticating its right to retrieve the user's

20 authentication information (with respect to the resource managers **206**) from the SSO service. It should be noted that step **304** may take place at any time (e.g., before or after the client terminal user performs a primary logon to the intermediary server). Thus, at step **306**, the

intermediary server **202** passes the user's primary account identity to the SSO service **204**. If the identity of the intermediary server **202** is validated, the intermediary server receives, in return, a set of user secondary identities (or "secondary account identities"). This is sometimes referred to as identity mapping and secondary authentication information retrieval. An illustrative user secondary identity is an user identity/password pair **216a** stored in the database **220** for use in authenticating the user to a given resource manager **206a**.

Generally, once the intermediary server has established its identity (with the SSO), it can be used to perform user secondary logons for any user. If desired, the SSO may include a set of mappings identifying the users for which the user is allowed to perform secondary logons. This would provide an added layer of security.

Returning back to **Figure 3**, the transaction flow then continues at step **308**, with the intermediary server **202** performing a single sign-on to the set of resource managers **206** using the set of user secondary account identities. Each logon from the intermediary server **202** to a respective resource manager via a preferably secure link **205** is sometimes referred to as a secondary logon

(as contrasted with the primary logon of the user to the intermediary server **202**). Thus, for example, in step **308**, the intermediary server uses a first user secondary identity **216a** to perform a secondary logon to resource manager **206a**, a second user secondary identity **216b** to perform a secondary logon to resource manager **206b**, and so on. The secondary logons may occur sequentially or concurrently.

At step **310**, after at least one or more of the secondary logons are complete, the resource request is passed to a given resource manager under the respective user secondary identity that is required to access the required resource. At step **312**, a response generated by the given resource manager is returned to the intermediary server. At step **314**, the response is forwarded from the intermediary server back to the client terminal to complete the transaction flow. Steps **310-314**, of course, may be repeated as often as necessary (e.g., using different user secondary identities with respect to different resource managers). Thus, for example, a first user request may be directed to a first resource manager **206a** under a first user secondary identity **216a**, a second user request may be directed to a

second resource manager 206b under a second user secondary identity 216b, and so forth.

Thus, according to the present invention, the intermediary server is provisioned with a delegation functionality, namely, the ability to access and use the SSO to map the user's primary account identity to the user's secondary account identities with respect to the different resource managers within the enterprise environment.

10 In the preferred embodiment, a user approaches the enterprise and claims an identity. The intermediary server challenges the user to authenticate himself/herself. Upon user primary logon (which establishes a user primary account identity), the
15 intermediary server uses its own identity to authenticate (to the SSO) its right to retrieve the user secondary account identities which, upon retrieval, will then be used by the intermediary server to perform user secondary logons to the respective resource managers. A preferred
20 technique for mapping a user primary account identity to a set of user secondary account identities is via a table lookup in the SSO database. Any other convenient technique may be used. Thus, once trusted intermediary server is connected to the SSO service over the mutually

authenticated secure link, the server authenticates itself, and then retrieves the user's authentication data with respect to the backend enterprise systems (managed by the resource managers).

5 The enterprise illustrated above, wherein the intermediary server is a web portal and the resource manages are backend legacy systems, is merely representative. The entire enterprise (including the backend systems) may be based on proprietary or open
10 protocols or, as illustrated, on combinations thereof. In a preferred embodiment, one or more of the resource managers may be replicated or mirrored, e.g., by a caching appliance. When multiple copies (or "instances") of a given resource manager exist, the intermediary
15 server **402** may include an appropriate load balancing routine, such as routine **425** in **Figure 4**, to manage how requests from multiple users (each having a user primary account identity) are serviced by the particular resource manager **406**. In this example, it is assumed that there
20 are three (3) instances **406a**, **406b** and **406c** of the resource manager. The load balancing routine may implement any convenient load balancing function, e.g., round robin, to direct user requests to the resource manager instances. A preferred load balancing routine is

a "least busy" routine wherein the routine 400 keeps track of how many requests have been sent to the resource manager instances and sends a "next" request to the instance of the resource with the fewest uncompleted,

5 outstanding requests. As also illustrated in **Figure 4**, the intermediary server 402 itself may be replicated or mirrored and then managed by a proxy 405 that manages the set of intermediary server instances. This provides a "high availability" architecture that is readily

10 scalable. In this embodiment, the multiple instances of the intermediary server need not keep track of which resource managers their counterparts send tasks. Each of the intermediary server instances could be coupled to all of the resource managers or a subset thereof. In an
15 illustrative embodiment, pairs of intermediary servers are assigned a set of resource managers, e.g., a first pair of servers are assigned a first set of resource managers, a second pair of servers are assigned a second pair of resource managers, and so on.

20 In an illustrative embodiment, the single sign-on service is any commercially available or proprietary sign-on service. A representative service is IBM Global Sign-On (GSO). Further details about IBM GSO are available from IBM's Internet web site.

The present invention enables a web-based business with disparate backend systems to create an integrated portal wherein users can have multiple account identities/passwords within the enterprise yet present a single user account paradigm to the outside world. Thus, for example, a user may have different accounts with a financial institution and desire to have different passwords for each account (e.g., a savings account, a checking account, or the like). Another example would be where a first company purchases a second company and desires to merge its backend computer systems. In such case, the merged entity may use the present invention to enable users to maintain their original access information via an integrated interface but provide appropriate backend processing to manage the accounts as necessary.

Having thus described our invention, what we claim as new and desire to secure by Letters Patent is set forth in the following claims.